




Picture								
Machine type	MS720*600 Fully automatic three-station thermoforming machine	MS720*600 Fully automatic four-station thermoforming machine	MS780*680 Fully automatic three-station thermoforming machine	MS780*680 Fully automatic four-station thermoforming machine	MS800*700 Fully automatic three-station thermoforming machine	MS800*700 Fully automatic four-station thermoforming machine	MS900*700 Fully automatic three-station thermoforming machine	MS780*850 Negative pressure integrated machine
Product	Cup lids, lunch boxes, sauce boxes, sauce dishes, plates, fruit folding boxes, cake folding boxes, trays, etc.	Products that need punching, such as cup lids with holes, lunch box lids, fruit boxes, cake boxes, etc.	Cup lids, lunch boxes, sauce boxes, sauce dishes, plates, fruit folding boxes, cake folding boxes, trays, etc.	Cup lids with holes, lunch box lids, fruit boxes, cake boxes, etc.	Cup lids, lunch boxes, sauce boxes, sauce dishes, plates, fruit folding boxes, cake folding boxes, trays, etc.	Products that need punching, such as cup lids with holes, lunch box lids, fruit boxes, cake boxes, etc.	Cup lids, lunch boxes, sauce boxes, sauce dishes, plates, fruit folding boxes, cake folding boxes, trays, etc.	Folding boxes, trays, and other common blister products
Applicable Materials	Starch degradation, photodegradation, PP, PS, PET, PVC, PLA, CPLA, CPET, OPS, calcium carbonate, and other sheets							PP、PS、PET、PVC
Machine size	12.5×2.3×2.8	13.6×2.3×2.8	13.5×2.3×2.8	14.5×2.5×2.8	14×2.5×2.8	16×2.5×2.8	14×2.5×2.8	12.5×2.3×2.8
Suitable sheet thickness (mm)	0.2-1.5							
Suitable sheet width (mm)	350-760		500-820			700-920		550-820

Machine type	5HP Box type air cooled water tank chiller parameters	10HP Box type air cooled water tank chiller parameters	Evaporator (Stainless steel/copper coil type)	The cold water flow rate is 3m3/h Heat exchange 13.5KW	The cold water flow rate is 6m3/h Heat exchange 27KW
Picture			Water tank (Stainless steel/rubber water tank)	Volume 68	Volume 130
Compressor (The original imported Panasonic compressor is adopted)	Refrigeration input power 3.75KW Refrigeration running current 3.75KW	Refrigeration input power 7.5KW Refrigeration running current 7.5KW	Tubing	Cold water frozen water media outlet 1inch Cold water frozen water media outlet 1inch	Cold water frozen water media outlet 1.5inch Cold water frozen water media outlet 1.5inch
Water pump375(W)	Lift MH18 0.5 Aoyuan clean water pump Flow rate 3m3/h	Lift MH18 1 Aoyuan clean water pump Flow rate 6m3/h	Temperature	Temperature control range 5-50°C Temperature control accuracy ±1.0°C	
Condenser (External finned type)	The cold water flow rate is 3m3/h Heat exchange 13.5KW	The cold water flow rate is 6m3/h Heat exchange 27KW	External dimension	1.25*0.63*1.28m	1.45*0.73*1.48m
Evaporator (Stainless steel/copper coil type)	The cold water flow rate is 3m3/h Heat exchange 13.5KW	The cold water flow rate is 6m3/h Heat exchange 27KW	Total weight	180KG	380KG

Machine type	Disposable cup single row fully automatic counting packaging machine	Disposable cup lids single row automatic counting packaging machine	Disposable cup double row Three row fully automatic counting packaging machine
Picture			
Max. packaging capacity	10-25 times/min	10-20 times/min	10-30 times/min
Packaging film width	150-500mm	150-400mm	
Bagging length	250-800mm (Can be customized according to user requirements)	300-900mm (Can be customized according to user requirements)	250-800mm (Can be customized according to user requirements)
Total power	3.5kw 220v		
Dimensions L*W*H	5.65*0.8*1.35m	2.4*1.74*1.32m	5.65*0.8*1.35m
Packing height	≤150mm	≤120mm	≤100mm
Gross weight	600kg	400kg	1200kg
Packing diameter	90-142mm	As per sample	0.03-0.06mm

Machine type	MODEL 850WASTE SHEETS ONLINE CRUSHER	MODEL 1000WASTE SHEETS ONLINE CRUSHER
Picture		
Main motor power	11KW, 380V/50HZ	
Discharge fan power	4KW, 380V/50HZ	
Tractor power	0.75KW, 380V/50HZ	
Grinding chamber inside diameter	950mm	
Bowl hole size	φ10mm	
L*W*H	1.8*1.6*2.4mm	2*1.3*2.4mm
Weights	1900kg	2000kg